

SXE

LABYRINTH TYPE BEARING PROTECTOR



► TECHNICAL FEATURES

- Advanced labyrinth seal design.
- Non contacting, zero friction, provide bearing protection.
- Dynamic O-ring design to prevent water & vapor entering the bearing housing during equipment cooling condition.
- Zero maintenance.
- Zero power consumption.
- Labyrinth Bearing Isolator mainly made by bronze, also available in an all stainless steel construction on special request.
- Smaller installation size.

► APPLICATION CONDITIONS

- Suitable for working conditions that comply with API 610 7th edition standard oil mist lubrication.
- Design for motors.
- Design of axial sealing ring for horizontal equipment operating at a speed of 20m/s for oil splash /grease lubrication and other linear conditions.
- To prevent oil mist lubrication leakage to the atmospheric side.


► TYPICAL INDUSTRIAL APPLICATIONS

- Aviation
- Aerospace
- Iron and Steel
- Power
- Water Conservancy
- Petrochemical
- Railway
- Marine
- Mining and Geology
- Construction Machinery

► PERFORMANCE CAPABILITIES

Standard Sizes	16mm-145mm(0.75"-5.875")
Typical incremental Size	1mm&0.062"
Temperature	-20 °C ~ +180 °C
Sliding velocity	≤ 20m/s

► PRODUCT STRUCTURE DIAGRAM



► THE COMPARISON CHART OF STANDARD MATERIAL

NO.	Name	Material
1	Stationary	Bronze
2	Rotary	316SS
3	O-Ring	FKM
4	O-Ring	FKM
5	O-Ring	FKM

FBU SEALING TECHNOLOGY (SUZHOU) CO.,LTD

No.183, Yinhe Road, High Tech Industrial Development
 Zone Changshu Suzhou, Jiangsu, 215533

+86-512-57011188
 sale@fbuseals.com
 www.fbuseals.com

FBU is certified to API Q1,
ISO 9001, ISO 14001

